Microsoft Basic Optical Mouse



Version Information	
Product Name	Microsoft® Basic Optical Mouse
Product Version	Microsoft Basic Optical Mouse v2.0
Mouse Version	Microsoft Basic Optical Mouse v2.0
Product Dimensions	
Mouse Length	4.47 inches (1134 millimeters)
Mouse Width	2.28 inches (57.9 millimeters)
Mouse Depth/Height	1.54 inches (39.2 millimeters)
Mouse Weight	3.27 ounces (92.8 grams)
Cable Length	72 +6/-0 inches (1830 +150/-0 millimeters)
Compatibility and Localization	1.2 1.6 3 11.6100 (1.000 1.100)
Interface	USB Compatible
Operating Systems	Microsoft Windows® Vista®, Windows XP, Windows 2000, and Windows 98 Mac OSX v.10.1-10.4
Top-line System Requirements	For a Windows-based PC: Requires a PC that meets the requirements for and has installed one of these operating systems: • Microsoft Windows Vista/XP/2000/98 • USB port • No software required For a Macintosh:
	Mac OSX v.10.1-10.4 USB port No software required
Compatibility Logos	Certified for Microsoft Windows Vista Mac logo Universal Mac logo Certified USB logo
Product Feature Performance	
Mouse Button Features	3 buttons including scroll wheel button
Right & Left Button Life	3.000,000 actuations
Wheel Button Life	250,000 actuations
Mouse Scrolling Features	Standard vertical scroll wheel
Wheel Vertical Scrolling Life	100,000 revolutions (away from user) at no more than 60 rotations per minute 300,000 revolutions (toward user) at no more than 60 rotations per minute
Storage Temperature & Humidity	-40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)
Operating Temperature & Humidity	14 °F (-10 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)
Tracking Technology	14 1 (10 0) to 104 1 (40 0) at <000 to 0000 (clause numbers)
Mouse Tracking System	Optical tracking system
Imaging Rate	Up to 3000 frames per second
X-Y Resolution	800 points per inch (31.5 points per millimeter)
Tracking Speed	Up to 20 inches (508 millimeters) per second
Certification Information	Top to 20 monte (600 minimizard) per decond
Country of Manufacture	People's Republic of China (PRC)
ISO 9001 Qualified Manufacturer	Yes
Agency and Regulatory Approvals	• FCC Declaration of Conformity (USA)
, gore, and regulatory , pp. or an	UL and cUL Notice of Approval (USA and Canada) ICES-003 report on file (Canada) TUV-T Certificate (Germany) CE Declaration of Conformity, Safety and EMC (European Union) GOST Certificate (Russia) VCCI Certificate (Japan) ACA/MED Declaration of Conformity (Australia and New Zealand) BSMI Certificate (Taiwan)
Windows Hardware Quality Labs (WHQL)	MIC Certificate (Korea) SASO Approval (Saudi Arabia) CB Scheme Certificate (International) ID: PENDING Microsoft Windows 2000, Windows XP (x86, x64), and Windows Vista (x86, x64)
TTINGOTTO FIGICIVATO QUAITY EADS (VITIQE)	15.1 Enterine tradector tradette 2000, tradette 700, xot, and tradette viola (xoo, xot)

Results stated herein are based on internal Microsoft testing. Individual results and performance may vary. Any device images shown are not actual size. This document is provided for informational purposes only and is subject to change without notice. Microsoft makes no warranty, express or implied, with this document or the information contained herein. Review any public use or publications of any data herein with your local legal counsel.

©2007 Microsoft Corporation.