

Microsoft® LifeChat® LX-1000



Version Information	
Product Name	Microsoft® LifeChat® LX-1000
Product Version	Microsoft LifeChat LX-1000
Headset Version	Microsoft LifeChat LX-1000
Product Dimensions	
Headset Length	7.21 inches (183 millimeters)
Headset Width	5.67 inches (144 millimeters)
Headset Depth/Height	1.90 inches (48.2 millimeters)
Headset Weight	2.86 ounces (81 grams)
Headset Cable Length	72 inches (1828 millimeters)
Compatibility and Localization	
Interface	Audio Jack
Operating Systems ¹	<ul style="list-style-type: none"> Windows® 8.1, Windows 8, Windows RT 8.1, Windows RT 8, and Windows 7 Macintosh OS X v10.7-10.9 Android 3.2 and 4.2 ¹ Advanced functionality not available with all devices and/or operating systems. See compatibility information at: www.microsoft.com/hardware/compatibility .
Top-line System Requirements	For a Windows-based PC: Requires a PC that meets the requirements for and has installed one of these operating systems: <ul style="list-style-type: none"> Microsoft Windows 8.1, Windows 8, or Windows 7 Analog audio input/output ports For a Macintosh PC: <ul style="list-style-type: none"> Macintosh OS X v10.1-10.7 Analog audio input/output ports Broadband required. Added charges may apply.
Software Version	No software required
Product Feature Performance	
Headset Features	<ul style="list-style-type: none"> Flexible microphone boom with acoustic noise cancellation In-line volume and microphone controls Compatible with Windows Live, AOL Instant Messenger, Yahoo! Messenger, Microsoft Office Communication, Skype, and QQ
Speaker Parameters	<ul style="list-style-type: none"> Sensitivity: 98 dB SPL/mW @ 1kHz Frequency Response: 80 Hz – 20 kHz Input Impedance: 34 Ohms +/- 5 ohm @ 1kHz Rated Input Power: 2x50mW Left/Right channel matching: 3dB
Microphone Parameters	<ul style="list-style-type: none"> Sensitivity: -50 dB SPL/mW @ 1kHz Frequency Response: 80 Hz – 20 kHz
Storage Temperature & Humidity	-40 F (-20 °C) to 140 °F (60 °C) with 65% relative humidity (non-condensing)
Operating Temperature & Humidity	32° F (0° C) to 104° F (40° C) with 80% relative humidity (non-condensing)
Certification Information	
Country of Manufacture	People's Republic of China (PRC)
ISO 9001 Qualified Manufacturer	Yes
ISO 14001 Qualified Manufacturer	Yes
Restriction on Hazardous Substances	This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.
FCC ID	This device complies with Part 15 of the FCC Rules and Industry Canada ICES-003. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Tested to comply with FCC standards. For home and office use. Model number: 1408, LifeChat LX-1000.
Agency and Regulatory Marks	<ul style="list-style-type: none"> EIP Pollution Control Mark, EPUP (China) CE Declaration of Conformity (European Union) WEEE (European Union) GOST Certificate (Russia) CITC Letter (Kingdom of Saudi Arabia)
Windows Certification Kit (WCK)	ID: 1608525 (32-bit) and 1608524 (64-bit) Microsoft Windows 8.1

Results stated herein are based on internal Microsoft testing. Individual results and performance may vary. Any device images shown are not actual size. This document is provided for informational purposes only and is subject to change without notice. Microsoft makes no warranty, express or implied, with this document or the information contained herein. Review any public use or publications of any data herein with your local legal counsel.

©2014 Microsoft Corporation. The names of actual companies and products mentioned herein may be trademarks of their respective owners.