Microsoft® LifeChat®ZX-6000

Microsoft Technical Data Sheet

Wireless Headset | Rechargeable

Version Information	
Product Version	Microsoft® LifeChat™ ZX-6000
Headset Version	Microsoft LifeChat ZX-6000 v1.0
Product Dimensions	
Headset Length	3.82 inches (97 millimeters)
Headset Width	2.80 inches (71 millimeters)
Headset Depth/Height	0.83 inches (21 millimeters)
Headset Weight	0.88 ounces +/- 0.18 ounces (25 grams +/- 5 grams)
Receiver Length	2.95 inches (75.1 millimeters)
Receiver Width	1.68 inches (42.5 millimeters)
Receiver Depth/Height	0.76 inches (19.4 millimeters)
Receiver Weight	10.6 ounces (300 grams)
Receiver Cable Length	118 inches (3000 millimeters)
Compatibility and Localization	
Interface	High-speed USB compatible with the USB 2.0 specification
Operating Systems	Microsoft Windows® Vista® and Windows XP Service Pack 2 (SP2)
Top-line System Requirements	Requires a PC that meets the requirements for and has installed one of these operating systems: Windows Vista or Windows XP
	Service Pack 2 (SP2)
	Pentium III 550 MHz (Pentium IV 1.4 GHz recommended) or faster
	60 MB hard drive space
	Powered USB 1.1 port (USB 2.0 recommended)
	CD-ROM drive
	Broadband Internet access required; access fees may apply
O ch 96 . 1	Microsoft LifeChat software version 1.0
Compatibility Logos	Certified Hi-Speed USB logo
Software Localization	Microsoft Lifechat software may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese,
	Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English language version will be installed.
Wireless Technology	language. Otherwise, the English ranguage version will be installed.
Wireless Platform	Proprietary 2.4 GHz Wireless
Wireless Flation	2.4 GHz frequency range
Wireless Range	
Tri ologo rango	32 feet (10 meters) typical. Note: RF range is affected by many factors, such as nearby metallic objects and relative positioning of the mouse and receiver.
Power Requirements	Initiative and receiver.
Power Source	1 Lithium-Polymer (3.7 volts, nominal)
Charge Life	8 hours continuous use talk time
Charging Time	4 hours typical
Product Feature Performance	Tribate y picti
Headset Features	• Digital USB
risaassi risaassi	Built-in unidirectional microphone with acoustic noise cancellation
	Built-in on/off and volume controls
	Four LEDs indicate out-of-range, battery life, charging, and connection status
	• Windows Live™ Call Button
Storage Temperature & Humidity	-40 °F (-40 °C) to 158 °F (70 °C) at 0% to 95% relative humidity (non-condensing)
Operating Temperature & Humidity	32° F (0° C) to 104° F (40° C) at 20% to 90% relative humidity (non-condensing)
Certification Information	
Country of Manufacture	People's Republic of China (PRC)
ISO 9001 Qualified Manufacturer	Yes
Agency and Regulatory Marks	FCC Declaration of Conformity (USA)
	UL and cUL Listed Accessory (USA and Canada)
	ICES-003 data on file (Canada)
	CE Declaration of Conformity, Safety and EMC (European Union)
	UL-GS Certificate (European Union)
	WEEE (European Union)
	VCCI Certificate (Japan)
	ACA/MED Declaration of Conformity (Australia and New Zealand)
	BSMI Certificate (Taiwan)
	MIC Certificate (Korea)
	CB Scheme Certificate (International)

Results stated herein are based on internal Microsoft testing. Individual results and performance may vary. Any device images shown are not actual size. This document is provided for informational purposes only and is subject to change without notice. Microsoft makes no warranty, express or implied, with this document or the information contained herein. Review any public use or publications of any data herein with your local legal counsel.

©2007 Microsoft Corporation. All rights reserved.