

[MS-DSCPM-Diff]:

Desired State Configuration Pull Model Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release version of this technology. This Open Specification is final documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional

development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Comments
3/30/2016	Released Preview Document.

PREVIEW

Table of Contents

1	Introduction	7
1.1	Glossary	7
1.2	References	8
1.2.1	Normative References	8
1.2.2	Informative References	8
1.3	Overview	8
1.4	Relationship to Other Protocols	8
1.5	Prerequisites/Preconditions	9
1.6	Applicability Statement	9
1.7	Vendor-Extensible Fields	9
1.8	Standards Assignments	9
2	Messages	10
2.1	Transport	10
2.2	Common Data Types	10
2.2.1	Namespaces	10
2.2.2	HTTP Headers	10
2.2.2.1	Content-Type	10
2.2.2.1.1	Application/octet-stream	11
2.2.2.1.2	Application/json	11
2.2.2.2	Checksum	11
2.2.2.3	ChecksumAlgorithm	11
2.2.2.4	ConfigurationName	11
2.2.2.5	ProtocolVersion	12
2.2.2.6	AgentId	12
2.2.2.7	Authorization	12
2.2.3	Common URI Parameters	12
2.2.3.1	ConfigurationId	13
2.2.3.2	ModuleName	13
2.2.3.3	ModuleVersion	13
2.2.3.4	AgentId	13
3	Protocol Details	14
3.1	GetConfiguration Versions 1.0 and 1.1 Details	14
3.1.1	Abstract Data Model	14
3.1.2	Timers	14
3.1.3	Initialization	14
3.1.4	Higher-Layer Triggered Events	14
3.1.5	Message Processing Events and Sequencing Rules	14
3.1.5.1	Action(ConfigurationId={ConfigurationId})/ConfigurationContent	15
3.1.5.2	GET	15
3.1.5.2.1	Request Body	16
3.1.5.2.2	Response Body	16
3.1.5.2.3	Processing Details	16
3.1.6	Timer Events	17
3.1.7	Other Local Events	17
3.2	GetModule Versions 1.0 and 1.1 Details	17
3.2.1	Abstract Data Model	17
3.2.2	Timers	17
3.2.3	Initialization	17
3.2.4	Higher-Layer Triggered Events	17
3.2.5	Message Processing Events and Sequencing Rules	17
3.2.5.1	Module(ConfigurationId={ConfigurationId},ModuleName={moduleName},ModuleVersion={moduleVersion})/ModuleContent	18
3.2.5.1.1	GET	18

3.2.5.1.1.1	Request Body	19
3.2.5.1.1.2	Response Body	19
3.2.5.1.1.3	Processing Details	19
3.2.6	Timer Events.....	20
3.2.7	Other Local Events.....	20
3.3	GetAction Versions 1.0 and 1.1 Details	20
3.3.1	Abstract Data Model.....	20
3.3.2	Timers	20
3.3.3	Initialization.....	20
3.3.4	Higher-Layer Triggered Events	20
3.3.5	Message Processing Events and Sequencing Rules	20
3.3.5.1	Action(ConfigurationId={ConfigurationId})/GetAction	21
3.3.5.1.1	POST	21
3.3.5.1.1.1	Request Body	22
3.3.5.1.1.2	Response Body	22
3.3.5.1.1.3	Processing Details	22
3.3.6	Timer Events.....	22
3.3.7	Other Local Events.....	22
3.4	SendStatusReport Versions 1.0 and 1.1 Details.....	23
3.4.1	Abstract Data Model.....	23
3.4.2	Timers	23
3.4.3	Initialization.....	23
3.4.4	Higher-Layer Triggered Events	23
3.4.5	Message Processing Events and Sequencing Rules	23
3.4.5.1	Node(ConfigurationID={ConfigurationId})/SendStatusReport.....	23
3.4.5.1.1	POST	23
3.4.5.1.1.1	Request Body	24
3.4.5.1.1.2	Response Body	25
3.4.5.1.1.3	Processing Details	25
3.4.6	Timer Events.....	25
3.4.7	Other Local Events.....	25
3.5	GetStatusReport Versions 1.0 and 1.1 Details.....	26
3.5.1	Abstract Data Model.....	26
3.5.2	Timers	26
3.5.3	Initialization.....	26
3.5.4	Higher-Layer Triggered Events	26
3.5.5	Message Processing Events and Sequencing Rules	26
3.5.5.1	Node(ConfigurationId={ConfigurationId})/StatusReports.....	26
3.5.5.1.1	GET	27
3.5.5.1.1.1	Request Body	28
3.5.5.1.1.2	Response Body	28
3.5.5.1.1.3	Processing Details	28
3.5.6	Timer Events.....	28
3.5.7	Other Local Events.....	28
3.6	GetConfiguration Version 2.0 Details	29
3.6.1	Abstract Data Model.....	29
3.6.2	Timers	29
3.6.3	Initialization.....	29
3.6.4	Higher-Layer Triggered Events	29
3.6.5	Message Processing Events and Sequencing Rules	29
3.6.5.1	Nodes(AgentId={AgentId})/ Configurations(ConfigurationName={ConfigurationName})/ConfigurationContent	30
3.6.5.2	GET.....	31
3.6.5.2.1	Request Body.....	32
3.6.5.2.2	Response Body	32
3.6.5.2.3	Processing Details	32
3.6.6	Timer Events.....	33

3.6.7	Other Local Events.....	33
3.7	GetModule Version 2.0 Details	33
3.7.1	Abstract Data Model.....	33
3.7.2	Timers	33
3.7.3	Initialization.....	34
3.7.4	Higher-Layer Triggered Events	34
3.7.5	Message Processing Events and Sequencing Rules	34
3.7.5.1	Modules(ModuleName={moduleName},ModuleVersion={moduleVersion})/ModuleContent	35
3.7.5.1.1	GET	35
3.7.5.1.1.1	Request Body	36
3.7.5.1.1.2	Response Body	36
3.7.5.1.1.3	Processing Details.....	36
3.7.6	Timer Events.....	37
3.7.7	Other Local Events.....	37
3.8	GetDscAction Version 2.0 Details	37
3.8.1	Abstract Data Model.....	37
3.8.2	Timers	38
3.8.3	Initialization.....	38
3.8.4	Higher-Layer Triggered Events	38
3.8.5	Message Processing Events and Sequencing Rules	38
3.8.5.1	Nodes(AgentId={AgentId})/GetDscAction	38
3.8.5.1.1	POST	39
3.8.5.1.1.1	Request Body	40
3.8.5.1.1.2	Response Body	40
3.8.5.1.1.3	Processing Details.....	40
3.8.6	Timer Events.....	41
3.8.7	Other Local Events.....	41
3.9	RegisterDscAgent Version 2 Details	41
3.9.1	Abstract Data Model.....	41
3.9.2	Timers	41
3.9.3	Initialization.....	42
3.9.4	Higher-Layer Triggered Events	42
3.9.5	Message Processing Events and Sequencing Rules	42
3.9.5.1	Nodes(AgentId={AgentId})	42
3.9.5.1.1	PUT	42
3.9.5.1.1.1	Request Body	44
3.9.5.1.1.2	Response Body	44
3.9.5.1.1.3	Processing Details.....	44
3.9.6	Timer Events.....	45
3.9.7	Other Local Events.....	45
3.10	SendReport Version 2.0 Details.....	45
3.10.1	Abstract Data Model.....	45
3.10.2	Timers	45
3.10.3	Initialization.....	46
3.10.4	Higher-Layer Triggered Events	46
3.10.5	Message Processing Events and Sequencing Rules	46
3.10.5.1	Nodes(AgentID={AgentId})/SendReport	46
3.10.5.1.1	POST	47
3.10.5.1.1.1	Request Body	48
3.10.5.1.1.2	Response Body	48
3.10.5.1.1.3	Processing Details.....	48
3.10.6	Timer Events.....	49
3.10.7	Other Local Events.....	49
3.11	GetReports Version 2.0 Details	49
3.11.1	Abstract Data Model.....	49
3.11.2	Timers	49

3.11.3	Initialization	50
3.11.4	Higher-Layer Triggered Events	50
3.11.5	Message Processing Events and Sequencing Rules	50
3.11.5.1	Nodes(AgentId={AgentId})/Reports	50
3.11.5.1.1	GET	50
3.11.5.1.1.1	Request Body	52
3.11.5.1.1.2	Response Body	52
3.11.5.1.1.3	Processing Details	52
3.11.6	Timer Events	52
3.11.7	Other Local Events	52
4	Protocol Examples	53
4.1	GetConfiguration Sequence	53
4.2	GetModule Sequence	53
4.3	GetAction Sequence	54
4.4	SendStatusReport Sequence	55
4.5	GetStatusReport Sequence	56
4.6	RegisterDscAgent Sequence	56
4.7	SendReport Sequence	57
4.8	GetDscAction Sequence	58
5	Security	59
5.1	Security Considerations for Implementers	59
5.2	Index of Security Parameters	59
6	Appendix A: Full JSON Schema	60
7	Appendix B: Product Behavior	64

1 Introduction

The Desired State Configuration Pull Model Protocol is based on the **Hypertext Transfer Protocol (HTTP)** (as specified in [RFC2616]). It is used for getting a client's **configuration** and **modules** from the server and for reporting back the client's status to the server.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative ~~and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in . Sections 1.5 and 1.9 are also normative but do not contain these terms.~~ All other sections and examples in this specification are informative.

1.1 Glossary

~~The~~This document uses the following terms ~~are specific to this document:~~

Augmented Backus-Naur Form (ABNF): A modified version of Backus-Naur Form (BNF), commonly used by Internet specifications. ABNF notation balances compactness and simplicity with reasonable representational power. ABNF differs from standard BNF in its definitions and uses of naming rules, repetition, alternatives, order-independence, and value ranges. For more information, see [RFC5234].

binary large object (BLOB): A collection of binary data stored as a single entity in a database.

checksum: A value that is the summation of a byte stream. By comparing the checksums computed from a data item at two different times, one can quickly assess whether the data items are identical.

configuration: Represents a **binary large object (BLOB)**. The protocol does not process the content of the **BLOB** and it is passed as-is to the higher layer.

Hypertext Transfer Protocol (HTTP): An application-level protocol for distributed, collaborative, hypermedia information systems (text, graphic images, sound, video, and other multimedia files) on the World Wide Web.

module: A BLOB in the Desired State Configuration Pull Model Protocol [MS-DSCPM]. The protocol does not process the content of the BLOB, and it is passed as it is to the higher layer.

Transmission Control Protocol (TCP): A protocol used with the Internet Protocol (IP) to send data in the form of message units between computers over the Internet. TCP handles keeping track of the individual units of data (called packets) that a message is divided into for efficient routing through the Internet.

Uniform Resource Identifier (URI): A string that identifies a resource. The URI is an addressing mechanism defined in Internet Engineering Task Force (IETF) Uniform Resource Identifier (URI): Generic Syntax [RFC3986].

Uniform Resource Locator (URL): A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [RFC1738].

universally unique identifier (UUID): A 128-bit value. UUIDs can be used for multiple purposes, from tagging objects with an extremely short lifetime, to reliably identifying very persistent objects in cross-process communication such as client and server interfaces, manager entry-point vectors, and RPC objects. UUIDs are highly likely to be unique. UUIDs are also known as globally unique identifiers (GUIDs) and these terms are used interchangeably in the Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the UUID. Specifically, the use of this term does not imply or require that the algorithms described in [RFC4122] or [C706] must be used for generating the UUID.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.rfc-editor.org/rfc/rfc2616.txt>

[RFC4122] Leach, P., Mealling, M., and Salz, R., "A Universally Unique Identifier (UUID) URN Namespace", RFC 4122, July 2005, <http://www.ietf.org/rfc/rfc4122.txt>

[RFC4234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 4234, October 2005, <http://www.rfc-editor.org/rfc/rfc4234.txt>

[RFC4634] Eastlake III, D. and Hansen, T., "US Secure Hash Algorithms (SHA and HMAC-SHA)", RFC 4634, July 2006, <http://www.ietf.org/rfc/rfc4634.txt>

[RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", RFC 4648, October 2006, <http://www.rfc-editor.org/rfc/rfc4648.txt>

1.2.2 Informative References

None.

1.3 Overview

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it in the Product Behavior appendix.

The Desired State Configuration Pull Model Protocol is used to register a client, to get the configuration and the module from the server, and to report back some elements to the server.

The protocol depends on HTTP for the transfer of all protocol messages, including the transfer of the binary data. In this specification, the entity that initiates the HTTP connection is referred to as the client, and the entity that responds to the HTTP connection is referred to as the server. With the Desired State Configuration Pull Model Protocol, binary data flows from the server to the client.

1.4 Relationship to Other Protocols

This protocol depends on HTTP as specified in [RFC2616]. HTTP version 1.1 is used with this protocol.

1.5 Prerequisites/Preconditions

This protocol does not provide a mechanism for a client to discover the **Uniform Resource Locator (URL)** of the server. Thus, it is a prerequisite that the client obtain the URL of the server before this protocol can be used.

1.6 Applicability Statement

The Desired State Configuration Pull Model Protocol is capable of downloading the configuration and modules from the server.

This document covers versioning issues in the following areas:

Supported Transports: This protocol can be implemented on top of HTTP, as specified in section 2.1.

Security and Authentication Methods: This protocol supports HTTP access authentication, as specified in [RFC2616] section 11.

Localization: This specification does not specify any localization-dependent protocol behavior.

1.7 Vendor-Extensible Fields

None.

1.8 Standards Assignments

None.

2 Messages

2.1 Transport

The Desired State Configuration Pull Model Protocol uses HTTP 1.1, as specified in [RFC2616], as the transport layer.

A **Transmission Control Protocol (TCP)** port has not been reserved for this protocol. TCP port 80 is commonly used because many HTTP proxy servers forward only HTTP traffic that uses port 80.

The protocol uses the access authentication functionality of the HTTP layer as specified in [RFC2616] section 11.

2.2 Common Data Types

None.

2.2.1 Namespaces

None.

2.2.2 HTTP Headers

The Desired State Configuration Pull Model Protocol uses existing headers as specified in [RFC2616].

Unless specified otherwise, the headers defined in this specification are used in both request and response messages.

If a client or server receives an HTTP header that is not defined in this section, or if the header is not defined in the current context (for example, receiving a request-only header in a response), the header **MUST** be interpreted as specified in [RFC2616].

This section defines the syntax of the HTTP headers that use the **Augmented Backus-Naur Form (ABNF)** syntax, as specified in [RFC4234].

The following table summarizes the HTTP headers defined by this specification.

Header	Description
Content-Type	Section 2.2.2.1
Checksum	Section 2.2.2.2

2.2.2.1 Content-Type

The Content-Type header specifies the type of data that is included in the body of the GET or POST request.

The syntax of the Content-Type header is defined as follows.

```
Ctype = "application/octet-stream" /  
      "application/json"  
Content-Type = "Content-Type: " Ctype CRLF /
```

```
"Content-Type: " "application/json" [";charset=UTF-8"] CRLF
```

Example: Content-Type: application/~~octetstring~~octet-stream

Content-Type: application/json; charset=UTF-8

2.2.2.1.1 Application/octet-stream

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it in the Product Behavior appendix.

This Content-Type is defined only for use in a request sent to the server and used in a GET ~~request~~response to get the module or configuration from a server.

2.2.2.1.2 Application/json

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it in the Product Behavior appendix.

This Content-Type is defined only for use in a request sent to the server and used in a POST ~~request~~response.

2.2.2.2 Checksum

The Checksum header field is defined only for use in a response message sent to a client as part of a GET request for the module and configuration.

```
Checksum = "Checksum" : DQUOTE Check-sumvalue DQUOTE CRLF
Check-sumvalue = BASE16 ; specified in [RFC4648]
/ 0x00 (Null Character)
```

Example: "Checksum": "8eDMbsSDig15Xx+B3msvRrDa5N1njaf5smVujQjhOeI="

"Checksum": ""

2.2.2.3 ChecksumAlgorithm

The ChecksumAlgorithm header field specifies the checksum algorithm used to generate the checksum.

```
ChecksumAlgorithm = "ChecksumAlgorithm" : DQUOTE Check-sumAlgorithmvalue DQUOTE CRLF
Check-sumAlgorithmvalue = "SHA-256" ; specified in [RFC4634]
```

Example: "ChecksumAlgorithm": "SHA-256"

2.2.2.4 ConfigurationName

The ConfigurationName header field SHOULD<1> isbe used in the request message sent to the server as part of a GET request for the configuration.

```
ConfigurationName+ = "ConfigurationName" : DQUOTE Configuration-Namevalue DQUOTE CRLF
Configuration-Namevalue+ = Element *(Element)
Element+ = DIGIT / ALPHA
```

Example: "ConfigurationName":"SubPart1"

2.2.2.5 ProtocolVersion

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The ProtocolVersion header field [SHOULD<2> isbe](#) used in the request message sent to the server as part of every request. The current version is hardcoded to 2.0.

```
ProtocolVersion+ = "ProtocolVersion" : DQUOTE ProtocolVersion-Namevalue DQUOTE CRLF
ProtocolVersion-Namevalue+ = Element . *(Element)
Element+ = DIGIT
```

Example: "ProtocolVersion":"2.0"

2.2.2.6 AgentId

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The AgentId header field [SHOULD<3> isbe](#) used in the request message sent to the server as part of every request. The AgentId is a unique GUID value generated once and stored in the Registry.

```
AgentId+ = "AgentId" : DQUOTE AgentId-Namevalue DQUOTE CRLF
AgentId-Namevalue : Element - *(Element)
Element+ = DIGIT / ALPHA / "-"
```

Example: "AgentId":"{34C8104D-F7BA-4672-8226-0809B0A3BEC3}"

2.2.2.7 Authorization

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The Authorization header field [SHOULD<4> isbe](#) used in the request message sent to the server as part of every request. The Shared authorization key is generated during the registration and serves to verify the payload sent to the server.

```
Authorization+ = "Authorization": Shared DQUOTE Authorization-Namevalue DQUOTE CRLF
Authorization-Namevalue+ = A signature generated from an HMAC hash of the request body.
Element+ = DIGIT / ALPHA / "-" / "+"
```

Example: "Authorization": "Shared GKtPgcocze1AM/pgc3LQzyGpDCRs15KoKx/2eXxIL8+w="

2.2.3 Common URI Parameters

The following table summarizes the set of common **URI** parameters defined by this protocol.

URI parameter	Section
ConfigurationId	Section 2.2.3.1

URI parameter	Section
ModuleName	Section 2.2.3.2
ModuleVersion	Section 2.2.3.3

2.2.3.1 ConfigurationId

The *ConfigurationId* parameter is a **universally unique identifier (UUID)** as specified in [RFC4122] section 3.

2.2.3.2 ModuleName

The *ModuleName* parameter is a string that is used by the server to identify a specific module.

MODULENAME = Element *(Element)

Element = DIGIT / ALPHA / 0x5f

2.2.3.3 ModuleVersion

The *ModuleVersion* parameter identifies the version of a module. It can be either an empty string or a string containing two to four groups of digits where the groups are separated by a period.

```

MODULEVERSION = MULTIDIGIT 0x2E MULTIDIGIT
                / MULTIDIGIT 0x2E MULTIDIGIT 0x2E MULTIDIGIT
                / MULTIDIGIT 0x2E MULTIDIGIT 0x2E MULTIDIGIT 0x2E MULTIDIGIT
                / 0x00 (NULL character)
MULTIDIGIT = DIGIT *[DIGIT]

```

2.2.3.4 AgentId

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The *AgentId* parameter SHOULD<5> be used in the request message sent to the server as part of every request. The *AgentId* is a unique GUID value generated once and stored in the Registry.

AgentId: "AgentId" : DQUOTE AgentId-Namevalue DQUOTE CRLF

AgentId-Namevalue: Element . *(Element)

Element: DIGIT / ALPHA

Example: "AgentId": "{34C8104D-F7BA-4672-8226-0809B0A3BEC3}"

3 Protocol Details

3.1 GetConfiguration **Versions 1.0 and 1.1** Details

The purpose of the GetConfiguration request is to get the configuration from the server. The GetConfiguration request maps to an HTTP GET request in which the Content-Type header is an application/octet-stream.

3.1.1 Abstract Data Model

The server MUST maintain a **ConfigurationTable** where each entry contains:

ServerConfigurationId: A unique combination of a ConfigurationId (section 2.2.3.1) and a ConfigurationName (section 2.2.2.4). The ConfigurationId MUST NOT be empty.

ServerConfigurationData: A **binary large object (BLOB)**. This data is not interpreted as part of this protocol and is passed on to higher layers as is.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

None.

3.1.5 Message Processing Events and Sequencing Rules

The server MUST match the ConfigurationId from the URL and, if specified, the ConfigurationName from the headers with the **ServerConfigurationId** in the **ConfigurationTable**. The server MUST use case-insensitive ordinal comparison to match the ConfigurationId (section 2.2.3.1) and ConfigurationName (section 2.2.2.4). If a match is found, the server MUST return **ConfigurationData** to the client with status code 200. If a match is not found, the server MUST return status code 404.

Resource	Description
Action(ConfigurationId={ConfigurationId})/ConfigurationContent	Gets the configuration from the server.

Request header	Usage	Value
ConfigurationName	Optional	As specified in section 2.2.2.4.

The responses to all the methods can result in the following status codes.

Status code	Reason phrase	Description
200	OK	Returned when the request is completed.

Status code	Reason phrase	Description
400	BAD REQUEST	The request could not be understood by the server due to malformed syntax.
404	NOT FOUND	Returned when the resource is not found.

The response message for this operation contains the following HTTP headers.

Response header	Usage	Value
checksum	Required	As specified in section 2.2.2.2.
checksumalgorithm	Required	As specified in section 2.2.2.3.

3.1.5.1 Action(ConfigurationId={ConfigurationId})/ConfigurationContent

The following HTTP method is allowed to be performed on this resource.

HTTP method	Description
GET	Gets the configuration from the server.

3.1.5.2 GET

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it in the Product Behavior appendix.

The URL specified by the client in the HTTP request line of the GET request identifies a "configuration point" targeted for the client. The server can have multiple configuration points and different configuration points can have different access permissions associated with them. For example, some configuration points require HTTP access authentication (as specified in [RFC2616] section 11). As another example, a configuration point could also allow only clients that connect from a specific IP address.

The syntax of the GetConfiguration request is defined as follows.

```
DSC-GetConfiguration-Request      = DSC-GetConfiguration-Req-Line
                                   DSC-GetConfigurationSetReq-Headers

DSC-GetConfiguration-Req-Line    = "GET" SP Request-URI SP HTTP-Version CRLF

Request-URI = Request-URI-Start DSC-GetConfigurationRequest-URI-End

DSC-GetConfigurationSetReq-Headers = *( DSC-GetConfigurationSetReq-Header-REQ
    / DSC-GetConfigurationSetReq-Header-OPT )

DSC-GetConfigurationSetReq-Header-REQ    = Host      ; section 14.23 of [RFC2616]

DSC-GetConfigurationSetReq-Header-OPT    = Connection ; section 14.10 of [RFC2616]
    / ConfigurationName ; section 2.2.2.4

DSC-GetConfigurationRequest-URI-End = "Action(ConfigurationId=" SQUOTE CONFIGURATIONID SQUOTE

RBRACKET FSLASH "ConfigurationContent"
SQUOTE = %x27 ; ' (Single Quote)
```

```
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
CONFIGURATIONID = UUID ; as specified in [RFC4122]
```

The syntax of the GetConfiguration response is defined as follows:

```
DSC-GetConfiguration-Response = Status-Line
DSC-GetConfigurationResp-Headers
DSC-GetConfigurationResp-Body

DSC-GetConfigurationResp-Headers = *( DSC-GetConfigurationResp-Header-REQ
    / DSC-GetConfigurationResp-Header-OPT
    / DSC-GetConfigurationResp-Body)

DSC-GetConfigurationResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
    / Content-Type ; section 2.2.2.1.1
    / Checksum ; section 2.2.2.2
    / ChecksumAlgorithm ; section 2.2.2.3

DSC-GetConfigurationResp-Header-OPT = Server ; section 14.38 of [RFC2616]

DSC-GetConfigurationResp-Body = Configuration ; section 3.1.5.1-12.2
```

The response message for this operation contains the following HTTP headers.

Response header	Usage	Value
checksum	Required	As specified in section 2.2.2.2.
checksumalgorithm	Required	As specified in section 2.2.2.3.

The response message for this method can result in the following status codes.

Status code	Description
200	Request completed.
400	Bad request.
404	The resource is not found.

3.1.5.2.1 Request Body

None.

3.1.5.2.2 Response Body

In the response body, configuration represents a BLOB.

3.1.5.2.3 Processing Details

The client gets the configuration from the server as content-type application/octet-stream in the response body for the GetConfiguration request. The server MUST send the **checksum** in the response headers as specified in section 2.2.2.2. The server MUST send the ChecksumAlgorithm in the response headers as specified in section 2.2.2.3. The server MUST generate the checksum using the following algorithm:

- Use the algorithm specified in section 2.2.2.3 to compute the hash of the response body as specified in [RFC4634] section 4.1.

- Perform base16 encoding of the computed hash as specified in [RFC4648] section 8.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 GetModule **Versions 1.0 and 1.1** Details

The GetModule request gets the module from the server. The GetModule request maps to HTTP GET request with content-type as application/octet-stream as part of the request.

3.2.1 Abstract Data Model

The server MUST maintain a **ModuleTable** in which each entry contains the following:

ServerConfigurationId: The ConfigurationId (section 2.2.3.1).

ServerModuleName: The ModuleName (section 2.2.3.2).

ServerModuleVersion: The ModuleVersion (section 2.2.3.3).

ServerModuleData: A BLOB of data. This data is not interpreted as part of this protocol and is passed on to higher layers as is.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

None.

3.2.5 Message Processing Events and Sequencing Rules

The server MUST match ConfigurationId from the URL with **ServerConfigurationId**, ModuleName with **ServerModuleName**, and ModuleVersion with **ServerModuleVersion** of the **ModuleTable**. The server uses case-insensitive ordinal comparison to match ConfigurationId, ModuleName, and ModuleVersion. For a **ServerConfigurationId**, the server MUST have a unique combination of **ServerModuleName** and **ServerModuleVersion**. **ServerModuleName** in the **ModuleTable** MUST NOT be empty. If a match is found, the server returns **ModuleData** to the client with status code 200. If a match is not found, the server returns status code 404.

Resource	Description
Module(ConfigurationId={ConfigurationId},ModuleName={moduleName},ModuleVersion={moduleVersion})/ModuleContent	Get the module from the

Resource	Description
	server.

The responses to all the methods can result in the following status codes.

Status code	Reason phrase	Description
200	OK	Request completed.
400	BAD REQUEST	The request could not be understood by the server due to malformed syntax.
404	NOT FOUND	Used in cases where the resource is not found.

The response message for this operation contains the following HTTP headers.

Response header	Usage	Value
Checksum	Required	As specified in section 2.2.2.2.
ChecksumAlgorithm	Required	As specified in section 2.2.2.3.

3.2.5.1 Module(ConfigurationId={ConfigurationId},ModuleName={moduleName},ModuleVersion={moduleVersion})/ModuleContent

The following HTTP method is allowed to be performed on this resource.

HTTP method	Description
GET	Gets the module from the server.

3.2.5.1.1 GET

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it in the Product Behavior appendix.

The URL specified by the client in the HTTP request line of the GET request identifies a "module point" targeted for the client. The server might have multiple module points and different modules points can have different access permissions associated with them. For example, some module points require HTTP access authentication (as specified in [RFC2616] section 11). Other module points allow only clients that connect from a specific IP address.

The syntax of the GetModule request is defined as follows.

```
DSC-GetModule-Request      = DSC-GetModule-Req-Line
                             DSC-GetModuleSetReq-Headers

DSC-GetModule-Req-Line    = "GET" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-GetModuleRequest-URI-End
DSC-GetModuleSetReq-Headers = *( DSC-GetModuleSetReq-Header-REQ
                                  / DSC-GetModuleSetReq-Header-OPT )
```

```

DSC-GetModuleSetReq-Header-REQ    = Host      ; section 14.23 of [RFC2616]

DSC-GetModuleSetReq-Header-OPT    = Connection ; section 14.10 of [RFC2616]
DSC-GetModuleRequest-URI-End = "Module(ConfigurationId=" SQUOTE CONFIGURATIONID SQUOTE
                                ",ModuleName=" SQUOTE MODULENAME SQUOTE
                                ",ModuleVersion=" SQUOTE MODULEVERSION SQUOTE
                                RBRACKET FSLASH "ModuleContent"

SQUOTE = %x27 ; ' (Single Quote)
MODULENAME = ModuleName; as specified in section 2.2.3.2
MODULEVERSION = *(DIGIT)[ 0x2E *(DIGIT)+)]; as specified in section 2.2.3.3
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
CONFIGURATIONID = UUID ; as specified in [RFC4122]

```

The syntax of the GetModule response is defined as follows:

```

DSC-GetModule-Response = Status-Line
                        DSC-GetModuleResp-Headers
                        DSC-GetModuleResp-Body

DSC-GetModuleResp-Headers = *( DSC-GetModuleResp-Header-REQ
                               / DSC-GetModuleResp-Header-OPT)

DSC-GetModuleResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
                              / Content-Type ; section 2.2.2.1.1
                              / Checksum ; section 2.2.2.2
                              / ChecksumAlgorithm ; section 2.2.2.3

DSC-GetModuleResp-Header-OPT = Server ; section 14.38 of [RFC2616]
DSC-GetModuleResp-Body = ModuleData ; section 3.2.5.1.1.2

```

The response message for this operation contains the following HTTP headers.

Response header	Usage	Value
checksum	Required	As specified in section 2.2.2.2.
checksumalgorithm	Required	As specified in section 2.2.2.3.

The response message for this method can result in the following status codes.

Status code	Description
200	Request completed.
400	Bad request.
404	The resource is not found.

3.2.5.1.1.1 Request Body

None.

3.2.5.1.1.2 Response Body

ModuleData represents a binary large object (BLOB) .

3.2.5.1.1.3 Processing Details

The client gets the module from the server as content-type application/octet-stream in the response body for GetModule request. The server MUST send the checksum in response headers as specified in section 2.2.2.2. The server MUST send the ChecksumAlgorithm in the response headers as specified in section 2.2.2.3. The server generates the checksum using the following algorithm:

- Use the algorithm specified in ChecksumAlgorithm to compute the hash of the response body as specified in [RFC4634] section 4.1.
- Perform base16 encoding of the computed hash as specified in [RFC4648] in section 8.

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

3.3 GetAction **Versions 1.0 and 1.1** Details

The purpose of the GetAction request is to get the action, as specified in section 3.3.5.1.1.2, from the server. GetAction request maps to HTTP POST request with content-type as application/json, as specified in Appendix A: Full JSON Schema (section 6), as part of the request.

3.3.1 Abstract Data Model

None.

3.3.2 Timers

None.

3.3.3 Initialization

None.

3.3.4 Higher-Layer Triggered Events

None.

3.3.5 Message Processing Events and Sequencing Rules

Resource	Description
Action(ConfigurationId={ConfigurationId})/GetAction	Get the action from the server.

The responses to all the methods can result in the following status codes.

Status code	Reason phrase	Description
200	OK	The Request completed.
400	BAD REQUEST	The request could not be understood by the server due to malformed syntax.

Status code	Reason phrase	Description
404	NOT FOUND	The resource is not found.

3.3.5.1 Action(ConfigurationId={ConfigurationId})/GetAction

The following HTTP method can be performed on this resource.

HTTP method	Description
POST	POSTs the data to the server and gets action from the server.

3.3.5.1.1 POST

The URL specified by the client in the HTTP request line of the POST request identifies the action point targeted for the client. The server can have multiple action points and different action points can have different access permissions associated with them. For example, some action points require HTTP access authentication (as specified in [RFC2616] section 11). Or, action points can also allow only clients that connect from a specific IP address.

The syntax of the GetAction request is defined as follows.

```

DSC-GetAction-Request = DSC-GetAction-Req-Line
                        DSC-GetActionSetReq-Headers
                        DSC-GetActionReq-Body

DSC-GetAction-Req-Line = "POST" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-GetActionRequest-URI-End

DSC-GetActionRequest-URI-End = "Action(ConfigurationId=" SQUOTE CONFIGURATIONID SQUOTE
                                RBRACKET FSLASH "GetAction"
                                SQUOTE = %x27 ; ' (Single Quote)
                                RBRACKET = %29 ; ) (Closing Bracket)
                                FSLASH = %2F ; / (Forward Slash)
                                CONFIGURATIONID = UUID ; as specified in [RFC4122]

DSC-GetActionSetReq-Headers = *( DSC-GetActionSetReq-Header-REQ
                                  / DSC-GetActionSetReq-Header-OPT )

DSC-GetActionSetReq-Header-REQ = Host ; section 14.23 of [RFC2616]
                                  / Accept ; section 14.1 of [RFC2616]
                                  / ContentType ' section 2.2.2.1.2
                                  / Content-Length ; section 14.13 of [RFC2616]

DSC-GetActionSetReq-Header-OPT = Connection ; section 14.10 of [RFC2616]
                                  / Expect ; section 14.20 of [RFC2616]

DSC-GetActionReq-Body = ActionRequest ; section 3.3.5.1.1.1

```

The syntax of the GetAction response is defined as follows:

```

DSC-GetAction-Response = Status-Line
DSC-GetActionResp-Headers
DSC-GetActionResp-Body

```

```

DSC-GetActionResp-Headers = *( DSC-GetActionResp-Header-REQ
                               / DSC-GetActionResp-Header-OPT)

DSC-GetActionResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
                               / Content-Type ; section 2.2.2.1.2

DSC-GetActionResp-Header-OPT = Server ; section 14.38 of [RFC2616]
DSC-GetActionResp-Body = ActionContent ; section 3.3.5.1.1.2

```

The response message for this method can result in the following status codes.

Status code	Description
200	Request completed.
400	Bad request.
404	The resource is not found.

3.3.5.1.1.1 Request Body

The ActionRequest packet is used by the client to transfer the following data fields:

Checksum: A checksum as specified in section 2.2.2.2.

ChecksumAlgorithm: The algorithm for the Checksum as specified in section 2.2.2.3.

NodeCompliant: A value indicating TRUE or FALSE.

StatusCode: A value indicating a number between -2147483648 and 2147483647.

ConfigurationName: An opaque name as specified in section 2.2.2.4.

3.3.5.1.1.2 Response Body

The ActionContent packet is used by the server to transfer the following data field:

Value: MUST be either GetConfiguration, Retry<6>, or OK.

3.3.5.1.1.3 Processing Details

The client sends the GetAction request with content-type as application/json to the server with a request body as specified in section 3.3.5.1.1.1. The client MUST include **Checksum** and **ChecksumAlgorithm** in the request body. The client SHOULD include **StatusCode** in the request body. The server responds back with content-type as application/json with response body as specified in section 3.3.5.1.1.2.

3.3.6 Timer Events

None.

3.3.7 Other Local Events

None.

3.4 SendStatusReport **Versions 1.0 and 1.1** Details

The SendStatusReport request SHOULD <7> ~~sends~~ send the status report, as specified in section 3.4.5.1.1.1, to the server. The SendStatusReport request maps to the HTTP POST request with content-type as application/json, as specified in Appendix A: Full JSON Schema (section 6), as part of the request.

3.4.1 Abstract Data Model

None.

3.4.2 Timers

None.

3.4.3 Initialization

None.

3.4.4 Higher-Layer Triggered Events

None.

3.4.5 Message Processing Events and Sequencing Rules

Resource	Description
Node(ConfigurationID={ConfigurationId})/SendStatusReport	Send the status report to the server.

The response to all the methods results in one of the following status codes.

Status code	Reason phrase	Description
200	OK	The request completed.
400	BAD REQUEST	The server could not read the request due to malformed syntax.
404	NOT FOUND	The resource is not found.

3.4.5.1 ~~Nodes~~Node(ConfigurationID={ConfigurationId})/SendStatusReport

The following HTTP method can be performed on this resource.

HTTP method	Description
POST	Posts the data to the server and gets status from the server.

3.4.5.1.1 POST

The URL specified by the client in the HTTP request line of the POST request identifies the status point targeted for the client. The server can have multiple status points that have different access permissions associated with them. For example, some status points require HTTP access authentication (as specified in [RFC2616] section 11). As another example, status points allow only clients that connect from a specific IP address.

The syntax of the SendStatusReport request is defined as follows.

```
DSC-SendStatusReport-Request = DSC-SendStatusReport-Req-Line
                               DSC-SendStatusReportSetReq-Headers
                               DSC-SendStatusReportReq-Body

DSC-SendStatusReport-Req-Line = "POST" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-SendStatusReportRequest-URI-End

DSC-SendStatusReportRequest-URI-End = "Nodes(ConfigurationId=" SQUOTE CONFIGURATIONID SQUOTE
RBRACKET FSLASH "SendStatusReport"
SQUOTE = %x27 ; ' (Single Quote)
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
ConfigurationID = UUID ; as specified in [RFC4122]

DSC-SendStatusReportSetReq-Headers = *( DSC-SendStatusReportSetReq-Header-REQ
/ DSC-SendStatusReportSetReq-Header-OPT )

DSC-SendStatusReportSetReq-Header-REQ = Host ; section 14.23 of [RFC2616]
/ Accept ; section 14.1 of [RFC2616]
/ ContentType ' section 2.2.2.1.2
/ Content-Length ; section 14.13 of [RFC2616]

DSC-SendStatusReportSetReq-Header-OPT = Connection ; section 14.10 of [RFC2616]
/ Expect ; section 14.20 of [RFC2616]

DSC-SendStatusReportReq-Body = StatusReportRequest ; section 3.4.5.1.1.1
```

The syntax of the SendStatusReport response is defined as follows:

```
DSC-SendStatusReport-Response = Status-Line
DSC-SendStatusReportResp-Headers
DSC-SendStatusReportResp-Body

DSC-SendStatusReportResp-Headers = *( DSC-SendStatusReportResp-Header-REQ
/ DSC-SendStatusReportResp-Header-OPT)

DSC-SendStatusReportResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
/ Content-Type ; section 2.2.2.1.2

DSC-SendStatusReportResp-Header-OPT = Server ; section 14.38 of [RFC2616]
DSC-SendStatusReportResp-Body = StatusReportContent ; section 3.4.5.1.1.2
```

The response message for this method can result in the following status codes.

Status code	Description
200	Request completed.
400	Bad request.
404	The resource is not found.

3.4.5.1.1.1 Request Body

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it in the Product Behavior appendix.

The StatusReportRequest packet is used by the client to transfer the following data fields:

JobId: The JobId parameter is a universally unique identifier (UUID) as specified in [RFC4122] section 3.

NodeName: A value that is used to identify the name of the client.

OperationType: A string value that identifies the type for the operation.

LCMVersion: A value that contains a string of two to four groups of digits where the groups are separated by a period that identifies the report generator on the client.

ReportFormatVersion: A value that ~~finds the identifier for the report.~~

~~**ConfigurationVersion:** A value that~~ contains a string of two to four groups of digits where the groups are separated by a period that finds the identifier for the report.

ConfigurationVersion: A value that contains a string of two to four groups of digits where the groups are separated by a period.

IpAddress: A value that identifies the IP addresses of the client separated by a semicolon (;).

StartTime: A value that identifies the start time of an operation on the client.

EndTime: A value that identifies the end time of an operation on the client.

~~**IpAddress:** A value that identifies the IP addresses of the client separated by a semicolon (;).~~

~~**StartTime:** A value that identifies the start time of an operation on the client.~~

~~**EndTime:** A value that identifies the end time of an operation on the client.~~

Errors: A valueset of string values that represents the errors for an operation on the client.

StatusData: A valueset of string values that represents the status of an operation on the client.

3.4.5.1.1.2 Response Body

The StatusReportContent packet does not contain any data.

3.4.5.1.1.3 Processing Details

The client sends the SendStatusReport request with content-type as application/json to the server with a request body as specified in section 3.3.5.1.1.1. The client MUST include JobId in the request body. The server responds back with status codes as specified in section 3.4.5.1.1.

3.4.6 Timer Events

None.

3.4.7 Other Local Events

None.

3.5 GetStatusReport Versions 1.0 and 1.1 Details

The GetStatusReport request SHOULD gets get the status report from the server, as specified in section 3.5.5.1.1. The GetStatusReport request maps to the HTTP GET request with content-type as application/json, as specified in Appendix A: Full JSON Schema (section 6), as part of the request.

3.5.1 Abstract Data Model

None.

3.5.2 Timers

None.

3.5.3 Initialization

None.

3.5.4 Higher-Layer Triggered Events

None.

3.5.5 Message Processing Events and Sequencing Rules

Resource	Description
Node(ConfigurationId={ConfigurationId})/Reports(JobId={JobId}))	Get the status report from the server.

The responses to all the methods can result in the following status codes.

Status Code	Reason Phrase	Description
200	OK	The request completed.
400	BAD REQUEST	The request could not be understood by the server due to malformed syntax.
404	NOT FOUND	The resource is not found.

3.5.5.1 NodesNode(ConfigurationId={ConfigurationId})/ReportsStatusReports

The following HTTP method can be performed on this resource.

HTTP Method	Description
GET	Gets the status report from the server.

3.5.5.1.1 GET

The URL specified by the client in the HTTP request line of the GET request identifies the "status point" targeted for the client. The server might have multiple status points and different status points might have different access permissions associated with them. For example, some status points require HTTP access authentication (as specified in [RFC2616] section 11). Other status points allow only clients that connect from a specific IP address.

The syntax of the GetStatusReport request is defined as follows.

```

DSC-GetStatusReport-Request = DSC-GetStatusReport-Req-Line
                             DSC-GetStatusReportSetReq-Headers

DSC-GetStatusReport-Req-Line = "GET" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-GetStatusReportRequest-URI-End

DSC-GetStatusReportRequest-URI-End = "NodesNode" (ConfigurationId=" SQUOTE CONFIGURATIONID
SQUOTE

RBRACKET FSLASH "Reports(JobId=" SQUOTE JOBID SQUOTE
RBRACKET
SQUOTE = %x27 ; ' (Single Quote)
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
ConfigurationID = UUID ; as specified in [RFC4122]
JOBID = UUID; as specified in [RFC4122]

DSC-GetStatusReportSetReq-Headers = *( DSC-GetStatusReportSetReq-Header-REQ
/ DSC-GetStatusReportSetReq-Header-OPT )

DSC-GetStatusReportSetReq-Header-REQ = Host ; section 14.23 of [RFC2616]
/ Accept ; section 14.1 of [RFC2616]
/ ContentType ' section 2.2.2.1.2
/ Content-Length ; section 14.13 of [RFC2616]

DSC-GetStatusReportSetReq-Header-OPT = Connection ; section 14.10 of [RFC2616]
/ Expect ; section 14.20 of [RFC2616]

```

The syntax of the GetStatusReport response is defined as follows:

```

DSC-GetStatusReport-Response = Status-Line
DSC-GetStatusReportResp-Headers
DSC-GetStatusReportResp-Body

DSC-GetStatusReportResp-Headers = *( DSC-GetStatusReportResp-Header-REQ
/ DSC-GetStatusReportResp-Header-OPT)

DSC-GetStatusReportResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
/ Content-Type ; section 2.2.2.1.2

DSC-GetStatusReportResp-Header-OPT = Server ; section 14.38 of [RFC2616]
DSC-GetStatusReportResp-Body = StatusReportContent ; section 3.4.5.1.1.2

```

The response message for this method can result in the following status codes.

Status code	Description
200	Request completed.

Status code	Description
400	Bad request.
404	The resource is not found.

3.5.5.1.1.1 Request Body

The StatusReportRequest packet is used by the client to transfer the following data fields:

JobId: A universally unique identifier (UUID) as specified in section 3.

NodeName: A value that identifies the name of the client.

OperationType: A value that identifies the type for the operation.

LCMVersion: A value that identifies the report generator on the client.

ReportFormatVersion: A value that finds the identifier for the report.

ConfigurationVersion: Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it in the Product Behavior appendix.

There is no information transferred in the request body.

A value that contains a string of two to four groups of digits where the groups are separated by a period.

IpAddress: A value that identifies the IP addresses of the client separated by a semicolon (;).

StartTime: A value that identifies the start time of an operation on the client.

EndTime: A value that identifies the end time of an operation on the client.

Errors: A value that represents the errors for an operation on the client.

StatusData: A value that represents the status of an operation on the client.

3.5.5.1.1.2 Response Body

StatusReportContent represents a BLOB.

3.5.5.1.1.3 Processing Details

The client sends the GetStatusReport request with the content-type as application/json to the server with a request body as specified in section 3.5.5.1.1.1. The server responds back with status codes as specified in section 3.5.5.1.1.

3.5.6 Timer Events

None.

3.5.7 Other Local Events

None.

3.6 GetConfiguration Version 2.0 Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The GetConfiguration request SHOULD<9> get the configuration from the server. The GetConfiguration request maps to an HTTP GET request in which the Content-Type header is an application/octet-stream.

3.6.1 Abstract Data Model

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The server MUST maintain a ConfigurationTable where each entry contains:

ServerAgentId: A unique combination of an AgentId (section 2.2.3.4) and a ConfigurationName (section 2.2.2.4). The AgentId MUST NOT be empty.

ServerConfigurationData: A BLOB that is not interpreted as part of this protocol and is passed on to higher layers as is.

3.6.2 Timers

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.6.3 Initialization

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.6.4 Higher-Layer Triggered Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.6.5 Message Processing Events and Sequencing Rules

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior

notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The server MUST match the AgentId (section 2.2.3.4) from the URL and, if specified, the ConfigurationName (section 2.2.2.4) from the headers with the ServerAgentId in the ConfigurationTable. The server MUST use case-insensitive ordinal comparison to match the AgentId and ConfigurationName. If a match is found, the server MUST return ServerConfigurationData to the client with status code 200. If a match is not found, the server MUST return status code 404.

Resource	Description
Nodes(AgentId={AgentId})/ Configurations(ConfigurationName={ConfigurationName})/ConfigurationContent	Gets the configuration from the server.

Request header	Usage	Value
ProtocolVersion	Required	Specified in section 2.2.2.5.

The responses to all the methods can result in the following status codes.

Status code	Reason phrase	Description
200	OK	Returned when the request is completed.
400	BAD REQUEST	The request could not be understood by the server due to malformed syntax.
401	UNAUTHORIZED	The client is not authorized.
404	NOT FOUND	Returned when the resource is not found.

The response message for this operation contains the following HTTP headers.

Response header	Usage	Value
checksum	Required	Specified in section 2.2.2.2.
checksumalgorithm	Required	See section 2.2.2.3.
configurationname	Optional	See section 2.2.2.4.
protocolversion	Required	See section 2.2.2.5.

3.6.5.1 Nodes(AgentId={AgentId})/ Configurations(ConfigurationName={ConfigurationName})/ConfigurationContent

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following HTTP method is allowed to be performed on this resource.

HTTP method	Description
<u>GET</u>	<u>Gets the configuration from the server.</u>

3.6.5.2 GET

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The URL specified by the client in the HTTP request line of the GET request identifies a "configuration point" targeted for the client. The server can have multiple configuration points and different configuration points can have different access permissions associated with them. For example, some configuration points require HTTP access authentication (as specified in [RFC2616] section 11). Or, a configuration point could allow only clients that connect from a specific IP address.

The syntax of the GetConfiguration request is defined as follows.

```

DSC-GetConfiguration-Request = DSC-GetConfiguration-Req-Line
                               DSC-GetConfigurationSetReq-Headers

DSC-GetConfiguration-Req-Line = "GET" SP Request-URI SP HTTP-Version CRLF

Request-URI = Request-URI-Start DSC-GetConfigurationRequest-URI-End

DSC-GetConfigurationSetReq-Headers = *( DSC-GetConfigurationSetReq-Header-REQ
                                          / DSC-GetConfigurationSetReq-Header-OPT )

DSC-GetConfigurationSetReq-Header-REQ = Host ; section 14.23 of [RFC2616]

DSC-GetConfigurationSetReq-Header-OPT = Connection ; section 14.10 of [RFC2616]
                                          / ConfigurationName ; section 2.2.2.4

DSC-GetConfigurationRequest-URI-End = "Nodes(AgentId=" SQUOTE AGENTID SQUOTE RBRACKET
                                       FSLASH (ConfigurationName=" SQUOTE CONFIGURATIONNAME SQUOTE
                                       RBRACKET FSLASH "ConfigurationContent"
                                       SQUOTE = %x27 ; ' (Single Quote)
                                       RBRACKET = %29 ; ) (Closing Bracket)
                                       FSLASH = %2F ; / (Forward Slash)
                                       AGENTID = UUID ; as specified in [RFC4122]
                                       CONFIGURATIONNAME as defined in 2.2.2.4

```

The syntax of the GetConfiguration response is defined as follows:

```

DSC-GetConfiguration-Response = Status-Line
                                DSC-GetConfigurationResp-Headers
                                DSC-GetConfigurationResp-Body

DSC-GetConfigurationResp-Headers = *( DSC-GetConfigurationResp-Header-REQ
                                       / DSC-GetConfigurationResp-Header-OPT
                                       / DSC-GetConfigurationResp-Body)

DSC-GetConfigurationResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
                                       / Content-Type ; section 2.2.2.1.1
                                       / Checksum ; section 2.2.2.2
                                       / ChecksumAlgorithm ; section 2.2.2.3

DSC-GetConfigurationResp-Header-OPT = Server ; section 14.38 of [RFC2616]

DSC-GetConfigurationResp-Body = Configuration ; section 3.6.5.2.2

```

The response message for this operation contains the following HTTP headers.

Response header	Usage	Value
Checksum	Required	See section 2.2.2.2.
ChecksumAlgorithm	Required	See section 2.2.2.3.
ProtocolVersion	Required	See section 2.2.2.5

The response message for this method can result in the following status codes.

Status code	Description
200	Request completed.
400	Bad request.
401	Not authorized.
404	The resource is not found.

3.6.5.2.1 Request Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.6.5.2.2 Response Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

In the response body, the configuration represents a BLOB.

3.6.5.2.3 Processing Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The client gets the configuration from the server as content-type application/octet-stream in the response body for the GetConfiguration request. The server MUST send the checksum in the response headers as specified in section 2.2.2.2. The server MUST send the ChecksumAlgorithm in the response headers as specified in section 2.2.2.3. The server MUST send the ProtocolVersion in the response headers as specified in section 2.2.2.5. The server generates the checksum using the following algorithm:

- Use the algorithm specified in section 2.2.2.3 to compute the hash of the response body as specified in [RFC4634] section 4.1.

- Perform base16 encoding of the computed hash as specified in [RFC4648] section 8.

3.6.6 Timer Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.6.7 Other Local Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.7 GetModule Version 2.0 Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The GetModule request SHOULD<10> get the module from the server. The GetModule request maps to the HTTP GET request with the content-type as application/octet-stream as part of the request.

3.7.1 Abstract Data Model

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The server MUST maintain a ModuleTable in which each entry contains the following:

ServerAgentId: The AgentId (section 2.2.2.6).

ServerModuleName: The ModuleName (section 2.2.3.2).

ServerModuleVersion: The ModuleVersion (section 2.2.3.3).

ServerModuleData: A BLOB of data. This data is not interpreted as part of this protocol and is passed on to higher layers as is.

3.7.2 Timers

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.7.3 Initialization

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.7.4 Higher-Layer Triggered Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.7.5 Message Processing Events and Sequencing Rules

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The server MUST match ModuleName with ServerModuleName, and ModuleVersion with the ServerModuleVersion of the ModuleTable. The server MUST use case-insensitive ordinal comparison to match ModuleName and ModuleVersion. For a ServerAgentId, the server MUST have a unique combination of ServerModuleName and ServerModuleVersion. ServerModuleName in the ModuleTable MUST NOT be empty. If a match is found, the server returns ModuleData to the client with status code 200. If a match is not found, the server returns status code 404.

<u>Resource</u>	<u>Description</u>
Modules(ModuleName={moduleName},ModuleVersion={moduleVersion})/ModuleContent	Get the module from the server.

Responses to the methods can result in one of the following status codes.

<u>Status code</u>	<u>Reason phrase</u>	<u>Description</u>
200	OK	Request completed.
400	BAD REQUEST	The request could not be understood by the server due to malformed syntax.
401	NOT AUTHORIZED	The client is not authorized.
404	NOT FOUND	Used in cases where the resource is not found.

The response message for this operation contains the following HTTP headers.

<u>Response header</u>	<u>Usage</u>	<u>Value</u>
AgentId	Required	See section 2.2.2.6.

Response header	Usage	Value
checksum	Required	See section 2.2.2.2.
checksumalgorithm	Required	See section 2.2.2.3.
protocolversion	Required	See section 2.2.2.5.

3.7.5.1 Modules(ModuleName={moduleName},ModuleVersion={moduleVersion})/ModuleContent

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following HTTP method can be performed on this resource.

HTTP method	Description
GET	Gets the module from the server.

3.7.5.1.1 GET

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The URL specified by the client in the HTTP request line of the GET request identifies a "module point" targeted for the client. The server might have multiple module points and different module points can have different access permissions associated with them. For example, some module points require HTTP access authentication (as specified in [RFC2616] section 11). Other module points allow only clients that connect from a specific IP address.

The syntax of the GetModule request is as follows.

```

DSC-GetModule-Request      = DSC-GetModule-Req-Line
                             DSC-GetModuleSetReq-Headers

DSC-GetModule-Req-Line    = "GET" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-GetModuleReq-URI-End
DSC-GetModuleSetReq-Headers = *( DSC-GetModuleSetReq-Header-REQ
    / DSC-GetModuleSetReq-Header-OPT )

DSC-GetModuleSetReq-Header-REQ    = Host      ; section 14.23 of [RFC2616]

DSC-GetModuleSetReq-Header-OPT    = Connection ; section 14.10 of [RFC2616]
DSC-GetModuleReq-URI-End = "Modules(ModuleName=" SQUOTE MODULENAME SQUOTE
    ",ModuleVersion=" SQUOTE MODULEVERSION SQUOTE
    RBRACKET FSLASH "ModuleContent"

SQUOTE = %x27 ; ' (Single Quote)
MODULENAME = ModuleName; as specified in section 2.2.3.3
MODULEVERSION = *(DIGIT)[ 0x2E *(DIGIT)]
RBRACKET = %29 ; ) (Closing Bracket)

```

FSLASH = %2F ; / (Forward Slash)

The syntax of the GetModule response is as follows:

```
DSC-GetModule-Response = Status-Line
                          _____
                          DSC-GetModuleResp-Headers
                          _____
                          DSC-GetModuleResp-Body

DSC-GetModuleResp-Headers = *( DSC-GetModuleResp-Header-REQ
                               / DSC-GetModuleResp-Header-OPT)

DSC-GetModuleResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
                               / Content-Type ; section 2.2.2.1.1
                               / Checksum ; section 2.2.2.2
                               / ChecksumAlgorithm ; section 2.2.2.3

DSC-GetModuleResp-Header-OPT = Server _____ ; section 14.38 of [RFC2616]
DSC-GetModuleResp-Body = ModuleData ; section 3.2.2.5.1.1.2
```

The response message for this operation contains the following HTTP headers.

<u>Response header</u>	<u>Usage</u>	<u>Value</u>
<u>checksum</u>	<u>Required</u>	<u>See section 2.2.2.2.</u>
<u>ProtocolVersion</u>	<u>Required</u>	<u>See section 2.2.2.5.</u>
<u>ChecksumAlgorithm</u>	<u>Required</u>	<u>See section 2.2.2.3.</u>

The response message for this method can result in the following status codes.

<u>Status code</u>	<u>Description</u>
<u>200</u>	<u>Request completed.</u>
<u>400</u>	<u>Bad request.</u>
<u>401</u>	<u>Not authorized.</u>
<u>404</u>	<u>The resource is not found.</u>

3.7.5.1.1.1 Request Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.7.5.1.1.2 Response Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

ModuleData represents a BLOB.

3.7.5.1.1.3 Processing Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The client gets the module from the server as content-type application/octet-stream in the response body for the GetModule request. The server MUST send the checksum in response headers as specified in section 2.2.2.2. The server MUST send the ChecksumAlgorithm in the response headers as specified in section 2.2.2.3. The server MUST send the ProtocolVersion in the response headers as specified in section 2.2.2.5. The server generates the checksum using the following algorithm:

- Use the algorithm specified in ChecksumAlgorithm to compute the hash of the response body as specified in [RFC4634] section 4.1.
- Perform base16 encoding of the computed hash as specified in [RFC4648] in section 8.

3.7.6 Timer Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.7.7 Other Local Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.8 GetDscAction Version 2.0 Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The GetDscAction request SHOULD<11> get the action, as specified in section 3.8.5.1.1.2, from the server. The GetDscAction request maps to HTTP POST request with content-type as application/json, as specified in Appendix A: Full JSON Schema (section 6), as part of the request.

3.8.1 Abstract Data Model

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.8.2 Timers

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.8.3 Initialization

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.8.4 Higher-Layer Triggered Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.8.5 Message Processing Events and Sequencing Rules

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

<u>Resource</u>	<u>Description</u>
<u>Nodes(AgentId={AgentId})/GetDscAction</u>	<u>Get the action from the server.</u>

The responses to all the methods can result in the following status codes.

<u>Status code</u>	<u>Reason phrase</u>	<u>Description</u>
<u>200</u>	<u>OK</u>	<u>The request completed.</u>
<u>400</u>	<u>BAD REQUEST</u>	<u>The request could not be understood by the server due to malformed syntax.</u>
<u>401</u>	<u>UNAUTHORIZED</u>	<u>The client is not authorized to send the request.</u>
<u>404</u>	<u>NOT FOUND</u>	<u>The resource is not found.</u>

3.8.5.1 Nodes(AgentId={AgentId})/GetDscAction

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior

notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following HTTP method is allowed to be performed on this resource.

HTTP method	Description
POST	POSTs the data to the server and gets action from the server.

3.8.5.1.1 POST

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The URL specified by the client in the HTTP request line of the POST request identifies the action point targeted for the client. The server can have multiple action points and different action points can have different access permissions associated with them. For example, some action points require HTTP access authentication (as specified in [RFC2616] section 11). Or, action points can also allow only clients that connect from a specific IP address.

The syntax of the GetDscAction request is defined as follows.

```
DSC-GetDscAction-Request = DSC-GetDscAction-Req-Line
                           DSC-GetDscActionSetReq-Headers
                           DSC-GetDscActionReq-Body

DSC-GetDscAction-Req-Line = "POST" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-GetDscActionRequest-URI-End

DSC-GetDscActionRequest-URI-End = "Nodes (AgentId=" SQUOTE AGENTID SQUOTE
RBRACKET FSLASH "GeDscAction"
SQUOTE = %x27 ; ' (Single Quote)
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
AGENTID = UUID ; as specified in [RFC4122]

DSC-GetDscActionSetReq-Headers = *( DSC-GetDscActionSetReq-Header-REQ
/ DSC-GetDscActionSetReq-Header-OPT )

DSC-GetDscActionSetReq-Header-REQ = Host ; section 14.23 of [RFC2616]
/ Accept ; section 14.1 of [RFC2616]
/ ContentType ' section 2.2.2.1.2
/ Content-Length ; section 14.13 of [RFC2616]

DSC-GetDscActionSetReq-Header-OPT = Connection ; section 14.10 of [RFC2616]
/ Expect ; section 14.20 of [RFC2616]

DSC-GetDscActionReq-Body = ActionRequest ; section 3.8.5.1.1.1
```

The syntax of the GetDscAction response is defined as follows:

```
DSC-GetDscAction-Response = Status-Line
DSC-GetDscActionResp-Headers
DSC-GetDscActionResp-Body

DSC-GetDscActionResp-Headers = *( DSC-GetDscActionResp-Header-REQ
```

/ DSC-GetDscActionResp-Header-OPT)

DSC-GetDscActionResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
/ Content-Type ; section 2.2.2.1.2

DSC-GetDscActionResp-Header-OPT = Server ; section 14.38 of [RFC2616]
DSC-GetDscActionResp-Body = ActionContent ; section 3.8.5.1.1.2

The response message for this method can result in the following status codes.

Status code	Description
<u>200</u>	<u>Request completed.</u>
<u>400</u>	<u>Bad request.</u>
<u>401</u>	<u>Unauthorized.</u>
<u>404</u>	<u>The resource is not found.</u>

3.8.5.1.1.1 Request Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The ActionRequest packet is used by the client to transfer the following data fields:

ClientStatus: An array of the following fields:

Checksum: A checksum as specified in section 2.2.2.2.

ChecksumAlgorithm: The algorithm for the Checksum as specified in section 2.2.2.3.

ConfigurationName: An opaque name as specified in section 2.2.2.4.

3.8.5.1.1.2 Response Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The ActionContent packet is used by the server to transfer the following data fields:

NodeStatus: MUST be either GetConfiguration, UpdateMetaConfiguration, Retry, or OK.

Details: An array of the following fields:

ConfigurationName: An opaque name as specified in section 2.2.2.4.

Status: MUST be either GetConfiguration, UpdateMetaConfiguration, Retry, or OK.

3.8.5.1.1.3 Processing Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior

notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The client sends the GetDscAction request with content-type as application/json to the server with a request body as specified in section 3.8.5.1.1.1. The client MAY include ClientStatus in the request body. The server responds back with content-type as application/json with response body as specified in section 3.8.5.1.1.2.

.

3.8.6 Timer Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.8.7 Other Local Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3-6-3.9 RegisterDscAgent Version 2 Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The RegisterDscAgent request **SHOULD<12>registers register** a client with a server, as specified in section 3.9.5.1.1.1. The RegisterDscAgent request maps to the HTTP PUT request with content-type as application/json, as specified in Appendix A: Full JSON Schema (section 6), as part of the request.

3-6-13.9.1 Abstract Data Model

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3-6-23.9.2 Timers

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3-6-33.9.3 Initialization

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3-6-43.9.4 Higher-Layer Triggered Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3-6-53.9.5 Message Processing Events and Sequencing Rules

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

Resource	Description
Nodes(AgentId={AgentId})	Register a client.

The responses to all the methods can result in the following status codes:

Status Code	Reason Phrase	Description
200	OK	The request completed.
400	BAD REQUEST	The request could not be understood by the server due to malformed syntax.
404	NOT FOUND	The resource is not found.

3-6-5-13.9.5.1 Nodes(AgentId={AgentId})

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following HTTP method can be performed on this resource:

HTTP Method	Description
PUT	Sends the registration to the server.

3-6-5-1-13.9.5.1.1 PUT

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The URL specified by the client in the HTTP request line of the PUT request identifies the "registration point" targeted for the client. The server might have multiple registration points and different registration points might have different access permissions associated with them. For example, some registration points require HTTP access authentication (as specified in [RFC2616] section 11). Other registration points allow only clients that connect from a specific IP address.

The syntax of the RegisterDscAgent request is defined as follows:

```
DSC-RegisterDscAgent-Request = DSC-RegisterDscAgent-Req-Line
                               DSC-RegisterDscAgentReq-Headers

DSC-RegisterDscAgent-Req-Line = "PUT" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-RegisterDscAgent-URI-End

DSC- RegisterDscAgentRequest-URI-End = "Nodes (Agentid=" SQUOTE AGENTID SQUOTE
RBRACKET FSLASH "Reports (JobId=" SQUOTE JOBID SQUOTE
RBRACKET
SQUOTE = %x27 ; ' (Single Quote)
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
AgentID = UUID ; as specified in [RFC4122]
RBRACKET
SQUOTE = %x27 ; ' (Single Quote)
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
AgentID = UUID ; as specified in [RFC4122]

DSC-RegisterDscAgentReq-Headers = *( DSC-RegisterDscAgentSetReq-Header-REQ
/ DSC-RegisterDscAgentSetReq-Header-OPT )

DSC- RegisterDscAgentSetReq-Header-REQ = Host ; section 14.23 of [RFC2616]
/ Accept ; section 14.1 of [RFC2616]
/ ContentType ' section 2.2.2.1.2
/ Content-Length ; section 14.13 of [RFC2616]

DSC- RegisterDscAgent SetReq-Header-OPT = Connection ; section 14.10 of [RFC2616]
/ Expect ; section 14.20 of [RFC2616]

DSC-RegisterDscAgentReq-Body = RegisterDscAgentRequest ; section 3.9.5.1.1.1
```

The syntax of the RegisterDscAgent response is defined as follows:

```
DSC-RegisterDscAgent-Response = Status-Line
DSC-RegisterDscAgentResp-Headers
DSC-RegisterDscAgentResp-Body

DSC-RegisterDscAgentResp-Headers = *( DSC-RegisterDscAgentResp-Header-REQ
/ DSC-RegisterDscAgentResp-Header-OPT)

DSC-RegisterDscAgentResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
/ Content-Type ; section 2.2.2.1.2

DSC-RegisterDscAgentResp-Header-OPT = Server ; section 14.38 of [RFC2616]
DSC-RegisterDscAgentResp-Body = StatusReportContent RegisterDscAgentContent; section
3.49.5.1.1.2
```

The response message for this method can result in the following status codes:

Status code	Description
200	Request completed.
400	Bad request.
404	The resource is not found.

~~3.6.5.1.21.1.1.1.1~~ Request Body

~~Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.~~

3.9.5.1.1.1 Request Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The RegisterDscAgentRequest packet is used by the client to transfer the following data fields:

~~**JobId:** A universally unique identifier (UUID) as specified in section 3.~~

nodeName: A value that identifies the name of the client.

LCMVersion: A value that identifies the report generator on the client.

ConfigurationNames: A set of values that define the configurations that MAY be targeted to this client.

IpAddress: A value that identifies the IP addresses of the client separated by a semicolon (;).

~~**CertificateAgentInformation:** A set of values describing the agent including LCMVersion, nodeName, and IpAddress.~~

CertificateInformation: A set of values describing the certificate generated on the client used for client validation, including Certificate FriendlyName, Certificate Issuer, Certificate NotAfter, Certificate NotBefore, Certificate Subject, Certificate PublicKey, Certificate Thumbprint, and Certificate Version.

~~3.6.5.1.2.13.9.5.1.1.2~~ Response Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

RegisterDscAgentContent represents a BLOB.

~~3.6.5.1.2.23.9.5.1.1.3~~ Processing Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior

notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The client sends the RegisterDscAgent request with the content-type as application/json to the server with a request body as specified in section 3.9.5.1.1.1. The server responds back with status codes as specified in section 3.69.5.1.1.

3.6-63.9.6 Timer Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.9.7 Other Local Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.10 SendReport Version 2.0 Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The SendReport request SHOULD<13> send the status report, as specified in section 3.10.5.1.1.1, to the server. The SendReport request maps to the HTTP POST request with content-type as application/json, as specified in Appendix A: Full JSON Schema (section 6), as part of the request.

3.10.1 Abstract Data Model

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.10.2 Timers

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.10.3 Initialization

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.10.4 Higher-Layer Triggered Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.10.5 Message Processing Events and Sequencing Rules

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

<u>Resource</u>	<u>Description</u>
Nodes(AgentID={AgentId})/SendReport	Send the status report to the server.

The response to all the methods results in one of the following status codes.

<u>Status code</u>	<u>Reason phrase</u>	<u>Description</u>
200	OK	The request completed.
400	BAD REQUEST	The server could not read the request due to malformed syntax.
401	UNAUTHORIZED	The client is not authorized to send a report.
404	NOT FOUND	The resource is not found.

3.10.5.1 Nodes(AgentID={AgentId})/SendReport

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following HTTP method can be performed on this resource.

<u>HTTP method</u>	<u>Description</u>
POST	Posts the data to the server and gets status from the server.

3.10.5.1.1 POST

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The URL specified by the client in the HTTP request line of the POST request identifies the status point targeted for the client. The server can have multiple status points that have different access permissions associated with them. For example, some status points require HTTP access authentication (as specified in [RFC2616] section 11). Other status points allow only clients that connect from a specific IP address.

The syntax of the SendReport request is defined as follows.

```
DSC-SendReport-Request = DSC-SendReport-Req-Line
                        DSC-SendReportSetReq-Headers
                        DSC-SendReportReq-Body

DSC-SendReport-Req-Line = "POST" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-SendReportRequest-URI-End

DSC-SendReportRequest-URI-End = "Node (AgentId=" SQUOTE AGENTID SQUOTE

RBRACKET FSLASH "SendReport"
SQUOTE = %x27 ; ' (Single Quote)
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
AgentID = UUID ; as specified in [RFC4122]

DSC-SendReportSetReq-Headers = *( DSC-SendReportSetReq-Header-REQ
/ DSC-SendReportSetReq-Header-OPT )

DSC-SendReportSetReq-Header-REQ = Host ; section 14.23 of [RFC2616]
/ Accept ; section 14.1 of [RFC2616]
/ ContentType ' section 2.2.2.1.2
/ Content-Length ; section 14.13 of [RFC2616]

DSC-SendReportSetReq-Header-OPT = Connection ; section 14.10 of [RFC2616]
/ Expect ; section 14.20 of [RFC2616]

DSC-SendReportReq-Body = ReportRequest ; section 3.10.5.1.1.1
```

The syntax of the SendReport response is defined as follows:

```
DSC-SendReport-Response = Status-Line
DSC-SendReportResp-Headers
DSC-SendReportResp-Body

DSC-SendReportResp-Headers = *( DSC-SendReportResp-Header-REQ
/ DSC-SendReportResp-Header-OPT)

DSC-SendReportResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
/ Content-Type ; section 2.2.2.1.2

DSC-SendReportResp-Header-OPT = Server ; section 14.38 of [RFC2616]
DSC-SendReportResp-Body = ReportContent ; section 3.10.5.1.1.2
```

The response message for this method can result in the following status codes.

Status code	Description
200	Request completed.
400	Bad request.

Status code	Description
401	Unauthorized.
404	The resource is not found.

3.10.5.1.1.1 Request Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The ReportRequest packet is used by the client to transfer the following data fields:

JobId: The JobId parameter is a universally unique identifier (UUID) as specified in [RFC4122]section 3.

OperationType: A value that identifies the type for the operation.

RefreshMode: A value that identifies whether the client is in PUSH or PULL mode.

Status: A value that identifies the status of the current operation.

LCMVersion: A value that identifies the report generator on the client.

ReportFormatVersion: A value that finds the identifier for the report.

ConfigurationVersion: A value that contains a string of two to four groups of digits where the groups are separated by a period.

NodeName: A value that is used to identify the name of the client.

IpAddress: A value that identifies the IP addresses of the client separated by a semicolon (;).

StartTime: A value that identifies the start time of an operation on the client.

EndTime: A value that identifies the end time of an operation on the client.

RebootRequested: A value that identifies whether the client requested a reboot.

Errors: A value that represents the errors for an operation on the client.

StatusData: A value that represents the status of an operation on the client.

AdditionalData: An array of key value pairs that represents additional data that the client is sending to the report server.

3.10.5.1.1.2 Response Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The ReportContent packet does not contain any data.

3.10.5.1.1.3 Processing Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The client sends the SendReport request with content-type as application/json to the server with a request body as specified in section 3.10.5.1.1.1. The client MUST include JobId in the request body. The server responds back with status codes as specified in section 3.10.5.1.1.

3.10.6 Timer Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.10.7 Other Local Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.11 GetReports Version 2.0 Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The GetReports request SHOULD get the status report from the server, as specified in section 3.11.5.1.1.1. The GetReports request maps to the HTTP GET request with content-type as application/json, as specified in Appendix A: Full JSON Schema (section 6), as part of the request.

3.11.1 Abstract Data Model

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.11.2 Timers

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.11.3 Initialization

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.11.4 Higher-Layer Triggered Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.11.5 Message Processing Events and Sequencing Rules

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

<u>Resource</u>	<u>Description</u>
<code>Nodes(AgentId={AgentId})/Reports(JobId={JobId}))</code>	Get the report from the server.

The responses to all the methods can result in the following status codes.

<u>Status Code</u>	<u>Reason Phrase</u>	<u>Description</u>
200	OK	The request completed.
400	BAD REQUEST	The request could not be understood by the server due to malformed syntax.
401	NOT AUTHORIZED	The client is not authorized to send the request.
404	NOT FOUND	The resource is not found.

3.11.5.1 Nodes(AgentId={AgentId})/Reports

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following HTTP method can be performed on this resource.

<u>HTTP Method</u>	<u>Description</u>
GET	Gets the report from the server.

3.11.5.1.1 GET

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The URL specified by the client in the HTTP request line of the GET request identifies the "reporting point" targeted for the client. The server might have multiple reporting points and different reporting points might have different access permissions associated with them. For example, some reporting points require HTTP access authentication (as specified in [RFC2616] section 11). Other reporting points allow only clients that connect from a specific IP address.

The syntax of the GetReports request is defined as follows.

```

DSC-GetReports-Request = DSC- GetReports -Req-Line
                        DSC- GetReportsSetReq-Headers
DSC-GetReports-Req-Line = "GET" SP Request-URI SP HTTP-Version CRLF
Request-URI = Request-URI-Start DSC-GetReportsRequest-URI-End

DSC-GetReportsRequest-URI-End = "Nodes(AgentId=" SQUOTE AGENTID SQUOTE

RBRACKET FSLASH "Reports(JobId=" SQUOTE JOBID SQUOTE
RBRACKET
SQUOTE = %x27 ; ' (Single Quote)
RBRACKET = %29 ; ) (Closing Bracket)
FSLASH = %2F ; / (Forward Slash)
AgentID = UUID ; as specified in [RFC4122]
JOBID = UUID; as specified in [RFC4122]

DSC-GetReportsSetReq-Headers = *( DSC-GetReportsSetReq-Header-REQ
/ DSC-GetReportsSetReq-Header-OPT )

DSC-GetReportsSetReq-Header-REQ = Host ; section 14.23 of [RFC2616]
/ Accept ; section 14.1 of [RFC2616]
/ ContentType ' section 2.2.2.1.2
/ Content-Length ; section 14.13 of [RFC2616]

DSC-GetReportsSetReq-Header-OPT = Connection ; section 14.10 of [RFC2616]
/ Expect ; section 14.20 of [RFC2616]

```

The syntax of the GetReports response is defined as follows:

```

DSC-GetReports-Response = Status-Line
DSC-GetReportsResp-Headers
DSC-GetReportsResp-Body

DSC-GetReportsResp-Headers = *( DSC-GetReportsResp-Header-REQ
/ DSC-GetReportsResp-Header-OPT)

DSC-GetReportsResp-Header-REQ = Content-Length ; section 14.13 of [RFC2616]
/ Content-Type ; section 2.2.2.1.2

DSC-GetReportsResp-Header-OPT = Server ; section 14.38 of [RFC2616]
DSC-GetReportsResp-Body = ReportContent ; section 3.11.5.1.1.2

```

The response message for this method can result in the following status codes.

Status code	Description
<u>200</u>	<u>Request completed.</u>
<u>400</u>	<u>Bad request.</u>
<u>401</u>	<u>Not authorized.</u>
<u>404</u>	<u>The resource is not found.</u>

3.11.5.1.1.1 Request Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

There is no information transferred in the request body.

3.11.5.1.1.2 Response Body

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

ReportsContent represents a BLOB.

3.11.5.1.1.3 Processing Details

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The client sends the GetReports request with the content-type as application/json to the server with a request body as specified in section 3.11.5.1.1.1. The server responds back with status codes as specified in section 3.11.5.1.1.2.

3.11.6 Timer Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

3.11.7 Other Local Events

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

None.

4 Protocol Examples

4.1 GetConfiguration Sequence

The following sequence occurs between a client and a server during a GetConfiguration request.

1. The client sends a GetConfiguration request.
2. If the server requires the client to be authenticated, the server and client exchange access authentication HTTP headers as specified in [RFC2616] section 11.
3. If authentication is not required, or if authentication has succeeded, the server responds with a "200 OK" HTTP response.
4. The client closes the TCP connection to the server.

The following figure shows a message sequence with a single GetConfiguration request.




Figure 1: Message sequence for a single GetConfiguration request

4.2 GetModule Sequence

The following sequence occurs between a client and a server during a GetModule request.

1. The client sends a GetModule request.
2. If the server requires the client to be authenticated, the server and client exchange access authentication HTTP headers as specified in [RFC2616] section 11.
3. If authentication is not required, or if authentication has succeeded, the server responds with a "200 OK" HTTP response.
4. The client closes the TCP connection to the server.

The following figure shows a message sequence with a single GetModule request.




Figure 2: Message sequence for a single GetModule request

4.3 GetAction Sequence

The following sequence occurs between a client and a server during a GetAction request.

1. The client sends a GetAction request.
2. If the server requires the client to be authenticated, the server and client exchange access authentication HTTP headers as specified in [RFC2616] section 11.
3. If authentication is not required, or if authentication has succeeded, the server responds with a "200 OK" HTTP response.
4. The client closes the TCP connection to the server.

The following figure shows a message sequence with a single GetAction request.




Figure 3: Message sequence with a single GetAction request

4.4 SendStatusReport Sequence

The following sequence occurs between a client and a server during a SendStatusReport request.

1. The client sends a SendStatusReport request.
2. If the server requires the client to be authenticated, the server and client exchange access authentication HTTP headers as specified in [RFC2616] section 11.
3. If authentication is not required, or if authentication has succeeded, the server responds with a HTTP 200 (OK) response.
4. The client closes the TCP connection to the server.

The following figure shows a message sequence with a single SendStatusReport request.




Figure 4: Message sequence with a single SendStatusReport

4.5 GetStatusReport Sequence

The following sequence occurs between a client and a server during a GetStatusReport request.

1. The client sends a GetStatusReport request.
2. If the server requires the client to be authenticated, the server and client exchange access authentication HTTP headers as specified in [RFC2616] section 11.
3. If authentication is not required, or if authentication has succeeded, the server responds with a HTTP 200 (OK) response.
4. The client closes the TCP connection to the server.

The following figure shows a message sequence with a single GetStatusReport request.




Figure 5: Message sequence with a single GetStatusReport

4.6 RegisterDscAgent Sequence

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following sequence occurs between a client and a server during a RegisterDscAgent request.

1. The client sends a RegisterDscAgent request.
2. If the server requires the client to be authenticated, the server and client exchange access authentication HTTP headers as specified in [RFC2616] section 11.
3. If authentication is not required, or if authentication has succeeded, the server responds with a HTTP 200 (OK) response.

4. The client closes the TCP connection to the server.

The following figure shows a message sequence with a single RegisterDscAgent request.




Figure 6: Message sequence with a single RegisterDscAgent

4.7 SendReport Sequence

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following sequence occurs between a client and a server during a SendReport request.

1. The client sends a SendReport request.
2. If the server requires the client to be authenticated, the server and client exchange access authentication HTTP headers as specified in [RFC2616] section 11.
3. If authentication is not required, or if authentication has succeeded, the server responds with a HTTP 200 (OK) response.
4. The client closes the TCP connection to the server.

The following figure shows a message sequence with a single SendReport request.




Figure 7: Message sequence with a single SendReport request

4.8 GetDscAction Sequence

Note: All of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

The following sequence occurs between a client and a server during a GetDscAction request.

1. The client sends a GetDscAction request.
2. If the server requires the client to be authenticated, the server and client exchange access authentication HTTP headers as specified in [RFC2616] section 11.
3. If authentication is not required, or if authentication has succeeded, the server responds with a "200 OK" HTTP response.
4. The client closes the TCP connection to the server.

The following figure shows a message sequence with a single GetDscAction request.




Figure 7: Message sequence with a single GetDscAction request

5 Security

5.1 Security Considerations for Implementers

The protocol is vulnerable to a hijacking attack in which the attacker guesses the value of the *ConfigurationId* (as specified in section 3.1.5.1), *JobId*, and/or *ModuleName*, *ModuleVersion* (as specified in section 3.2.5.1), and the TCP port number used by the client. This approach works because the attacker can establish its own TCP connection to the server and send a request by using the victim's *ConfigurationId*, *JobId*, and/or *ModuleName*, *ModuleVersion* value. To mitigate the attack, make *ConfigurationId* and *JobId* random values. Also, if HTTP access authentication is used, the server ought to authenticate access at least once on each new URL or TCP connection.

5.2 Index of Security Parameters

Security parameter	Section
HTTP access authentication	As specified in section 2.1.

6 Appendix A: Full JSON Schema

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it in the Product Behavior appendix.

```
{
  "title": "GetAction request schema",
  "type": "object",
  "properties": {
    "Checksum": {
      "type": ["string", "null"]
    },
    "ConfigurationName": {
      "type": ["string", "null"]
    },
    "NodeCompliant": {
      "type": "boolean"
    },
    "ChecksumAlgorithm": {
      "enum": ["SHA-256"],
      "description": "Checksum algorithm used to generate checksum"
    },
    "StatusCode": {
      "type": "integer"
    }
  },
  "required": ["Checksum", "NodeCompliant", "ChecksumAlgorithm"]
}

{
  "title": "GetAction response",
  "type": "object",
  "properties": {
    "value": {
      "enum": ["OK", "GetConfiguration", "Retry", "UpdateMetaConfiguration"],
      "required": "true"
    }
  }
}

{
  "title": "GetDscAction request schema (AgentID)",
  "type": "object",
  "properties": {
    "ClientStatus": {
      "type": "array",
      "minItems": 1,
      "items": [
        {
          "type": "object",
          "properties": {
            "Checksum": {
              "type": [ "string", "null" ]
            },
            "ConfigurationName": {
              "type": [ "string", "null" ]
            },
            "ChecksumAlgorithm": {
              "enum": [ "SHA-256" ],
              "description": "Checksum algorithm used to generate checksum"
            }
          }
        }
      ]
    }
  }
}
```

```

        "uniqueItems": true
    }
}
}
{
    "title": "GetDscAction response",
    "type": "object",
    "properties": {
        "NodeStatus": {
            "enum": [ "OK", "RETRY", "GetConfiguration", "UpdateMetaConfiguration" ],
            "required": "true"
        },
        "Details": {
            "type": "array",
            "required": false,
            "items": [
                {
                    "type": "object",
                    "required": true,
                    "properties": {
                        "ConfigurationName": {
                            "type": "string",
                            "required": true
                        },
                        "Status": {
                            "enum": [ "OK", "RETRY", "GetConfiguration",
"UpdateMetaConfiguration" ],
                            "required": true
                        }
                    }
                }
            ]
        }
    }
}
{
    "title": "SendReport request schema",
    "type": "object",
    "properties": {
        "JobId": {
            "type": [ "string", "null" ],
            "required": "true"
        },
        "OperationType": {
            "type": [ "string", "null" ]
        },
        "RefreshMode": {
            "enum": [ "Push", "Pull" ]
        },
        "Status": {
            "type": [ "string", "null" ]
        },
        "LCMVersion": {
            "type": [ "string", "null" ]
        },
        "ReportFormatVersion": {
            "type": [ "string", "null" ]
        },
        "ConfigurationVersion": {
            "type": [ "string", "null" ]
        },
        "NodeName": {
            "type": [ "string", "null" ]
        },
        "IpAddress": {
            "type": [ "string", "null" ]
        },
        "StartTime": {

```

```

        "type": [ "string", "null" ]
    },
    "EndTime": {
        "type": [ "string", "null" ]
    },
    "RebootRequested": {
        "enum": [ "True", "False" ]
    },
    "Errors": {
        "type": [ "string", "null" ]
    },
    "StatusData": {
        "type": [ "string", "null" ]
    },
    "AdditionalData": {
        "type": "array",
        "required": false,
        "items": [
            {
                "type": "object",
                "required": true,
                "properties": {
                    "Key": {
                        "type": "string",
                        "required": true
                    },
                    "Value": {
                        "type": "string",
                        "required": true
                    }
                }
            }
        ]
    }
}

{
    "title": "RegisterDscAgent request",
    "type": "object",
    "properties": {
        "AgentInformation": {
            "type": "object",
            "properties": {
                "LCMVersion": {
                    "type": [ "string", "null" ]
                },
                "NodeName": {
                    "type": [ "string", "null" ]
                },
                "IPAddress": {
                    "type": [ "string", "null" ]
                }
            }
        },
        "RegistrationInformation": {
            "type": "object",
            "properties": {
                "RegistrationMessageType" : {
                    "type": [ "string", "null" ]
                },
                "CertificateInformation": {
                    "type": "object",
                    "properties": {
                        "FriendlyName": {
                            "type": [ "string", "null" ]
                        },
                        "Issuer": {
                            "type": [ "string", "null" ]
                        }
                    }
                }
            }
        }
    }
}

```

```
        "NotAfter": {
            "type": [ "string", "null" ]
        },
        "NotBefore": {
            "type": [ "string", "null" ]
        },
        "Subject": {
            "type": [ "string", "null" ]
        },
        "PublicKey": {
            "type": [ "string", "null" ]
        },
        "Thumbprint": {
            "type": [ "string", "null" ]
        },
        "Version": {
            "type": [ "integer", "null" ]
        }
    }
}
},
"ConfigurationNames": {
    "type": [ "string", "null" ]
}
}
}
}
```

PREVIEW

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

Note: Some of the information in this section is subject to change because it applies to a preliminary product version, and thus may differ from the final version of the software when released. All behavior notes that pertain to the preliminary product version contain specific references to it as an aid to the reader.

- Windows 7 operating system
- Windows Server 2008 R2 operating system
- Windows Server 2012 operating system
- Windows 8.1 operating system
- Windows Server 2012 R2 operating system
- Windows 10 operating system
- Windows Server 2016 Technical Preview operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

<1> Section 2.2.2.4: The ConfigurationName header field is available in Windows 10 and Windows Server 2016 Technical Preview ~~only~~.

<2> Section 2.2.2.5: The ProtocolVersion header field is available in Windows 10 v1511 operating system and Windows Server 2016 Technical Preview ~~only~~.

<3> Section 2.2.2.6: The AgentId header field is available in Windows 10 v1511 and Windows Server 2016 Technical Preview ~~only~~.

<4> Section 2.2.2.7: The Authorization header field is available in Windows 10 v1511 and Windows Server 2016 Technical Preview only.

<5> Section 2.2.3.4: [AgentId is implemented in Windows Server 2016 Technical Preview.](#)

<6> Section 3.3.5.1.1.2: Retry is available in Windows 10 and Windows Server 2016 Technical Preview only.

<7> Section 3.4: The SendStatusReport request is available in Windows Server 2016 Technical Preview and Windows 10 only.

<8> Section 3.5: The GetStatusReport request is available in Windows 10 and Windows Server 2016 Technical Preview ~~only~~.

<9> Section 3.6: [GetConfiguration Version 2.0 is implemented in Windows Server 2016 Technical Preview.](#)

<10> Section 3.7: [GetModule Version 2.0 is implemented in in Windows Server 2016 Technical Preview.](#)

<11> Section 3.8: [GetDscAction is implemented in Windows Server 2016 Technical Preview.](#)

<12> Section 3.9: The RegisterDscAgent request is available in Windows ~~10 v1511~~ and Windows Server 2016 Technical Preview only.

<13> Section 3.10: [The SendReport request is implemented in Windows Server 2016 Technical Preview.](#)

<14> Section 3.11: [GetReports is implemented in Windows Server 2016 Technical Preview.](#)

PREVIEW